



24 Hour Emergency Service

Rentals • Sales • Service

(800) 627-2653

25 HP, 150 psig High Pressure Steam Boiler

Cole Industrial's 25 HP (862 lbs/hr) Cleaver-Brooks firetube steam boiler, 150 psig design pressure, firing natural gas. Includes the following:

- 25 HP Steam Boiler
- Gas Pressure Regulator
- Valve Trim (main steam valve, safety relief, blow-down)
- Stub Stack (4'L) shipped
- (2) McDonnell-Miller Float Assemblies
- High/Low Firing Operation
- 30 amp Fused Disconnect Box
- Honeywell Fluid Power Gas Valve
- Honeywell 780 Burner Controller
- Pilot System w/ Electric Ignition
- Pre-piped & wired Gas Train



Fuel Consumption:

Natural Gas: 1,050 SCFH @ 2 psig

Connection Sizes:

Main Steam: 2" NPT
Gas: 1-1/4" NPT
Blowdown/Drain: 1" NPT
Feedwater: 1" NPT

Electrical Power Requirements:

240-480 VAC, 3 ph, 60 Hz
18-22 FLA running (depending on voltage)

Dimensions & Weights:

Length: 9'6"
Width: 46"
Height: 58-1/2"
Shipping Weight: 3,500 lbs
Operating Weight: 5,550 lbs



HEADQUARTERS:

5924 203rd St. S.W.
Lynnwood, WA 98036
Ph: 425/774-6602
Fax: 425/775-2272

N. OREGON OFFICE:

19860 SW 129th
Tualatin, OR 97210
Ph: 503/972-0595
Fax: 503/972-0596

YAKIMA OFFICE:

1502 S. 36th Ave.
Yakima, WA 98902
Ph: 509/457-5015
Fax: 509/457-5160

S. OREGON OFFICE:

750 Industrial Circle
White City, OR 97503
Ph: 541/826-2421
Fax: 541/826-2971

IDAHO OFFICE:

2000 Century Way
Boise, ID 83709
Ph: 208/465-8005

ALASKA OFFICE:

2805 Valleywood Dr. Apt A
Anchorage, AK 99517
Ph: 907/222-2715
Fax: 907/222-2920