



24 Hour Emergency Service

Rentals • Sales • Service

(800) 627-2653

250 HP, 200 psig Skid-Mounted Boiler

Cole Industrial's 250 HP (8,625 lbs/hr) skid-mounted Cleaver-Brooks Firetube Steam Boiler is designed at 200 psig, firing natural gas and/or #2 fuel oil. Includes the following:

- Honeywell 7800 Series Combustion Controls
- Gas Pressure Regulator, Gas Train
- Oil System with Pump & Air Compressor
- Pilot System w/ Electric Ignition
- Forced-draft fan, 7.5 HP Motor & Starter
- Steam Pressure Gauge
- Water Column & Sight Glass
- Float-type Low Water Cutoffs
- Low Water and Flame Failure Alarms
- Valve Trim (maint steam valve, safety relief valves, pre-piped FW stop & check valves)
- Stub Stack (4'L, shipped loose)
- Bottom & Control Blowdown Valves



Fuel Consumption:

Natural Gas: 10,000 SCFH @ 5 psig
#2 Fuel Oil: 75 gallons per hour

Connection Sizes:

Main Steam 6"-300# Flanged
Gas: 1-1/4" - NPT Inlet
#2 Oil: 1/2" Supply & Return
Feedwater: 1" NPT
Flue Outlet: 20" OD FLG
Bottom Blowdown: 1-1/2" NPT

Electrical Power Requirements:

240-480 VAC, 3 ph, 60 Hz
55-34 FLA (depending on voltage)

Dimensions & Weights:

Length: 16'8"
Width: 9'3"
Height: 8'8"
Shipping Weight: 22,800 lbs
Operating Weight: 36,700 lbs



HEADQUARTERS:

5924 203rd St. S.W.
Lynnwood, WA 98036
Ph: 425/774-6602
Fax: 425/775-2272

N. OREGON OFFICE:

19860 SW 129th
Tualatin, OR 97210
Ph: 503/972-0595
Fax: 503/972-0596

YAKIMA OFFICE:

1502 S. 36th Ave.
Yakima, WA 98902
Ph: 509/457-5015
Fax: 509/457-5160

S. OREGON OFFICE:

750 Industrial Circle
White City, OR 97503
Ph: 541/826-2421
Fax: 541/826-2971

IDAHO OFFICE:

2000 Century Way
Boise, ID 83709
Ph: 208/465-8005

ALASKA OFFICE:

Anchorage, AK
Ph: 907/203-0133